

3200 Premium Wax/Resin

Ribbon	Ribbon Type		Compatible Material	Print Speed	Temperature Resistance	Smear/Scratch Resistance	Chemical Resistance
2300	Wax	Standard	Uncoated/Coated Paper				
2100	Wax	High-Performance	Uncoated/Coated Paper				
3400	Wax/Resin	High-Performance	Uncoated/Coated Paper Matte Synthetics				
3200	Wax/Resin	Premium	Uncoated/Coated Paper Matte Synthetics				
4800	Resin	Performance	Matte/Gloss Synthetics				
5095	Resin	High-Performance	Matte/Gloss Synthetics				
5100	Resin	Premium	Matte/Gloss Synthetics				
Image Lock™	Resin	Specialist	Z-Xtreme™ 5000T				

Additional Features

- Extremely versatile, suitable for a wide variety of materials. Can be used on both paper and synthetics, reducing the need to stock multiple ribbons
- Good smear and scratch resistance on Zebra paper and matte synthetic labels
- Can achieve high print speeds of 254mm/sec (10ips), even on rotated barcodes
- Resistant to many everyday chemicals and when used with Z-Xtreme™ 4000T series materials, can withstand harsh chemical exposure

Suggested Applications

- Box, pallet and shipping labels
- Outdoor product tag and labelling for wire, cable and fabricated parts
- Indoor and outdoor product and shelf-edge labelling
- Labels subject to moderate abrasion or friction
- Pharmacy and pharmaceutical labelling
- Applications exposed to solvents, steam, alkali or acid solutions

UL Recognised and CSA Certified

Approved for use with the following materials:

- Z-Xtreme™ 4000T White High-Tack
- Z-Xtreme™ 4000T Silver High-Tack
- Z-Xtreme™ 4000T White



Technical Specifications

	Description
Colour	Black
Base Film	Polyester
Base Film Caliper	4.5 microns
Total Caliper	9 microns
Scanning Capabilities	IR and Visible Light

Ribbon Compliance

Compliance	3200
REACH/ Substances of Very High Concern (SVHC)	✓
RoHS	✓
Dodd-Frank Act (Conflict Minerals)	
Toxic Substances Control Act of 1976	✓
Carcinogenic, Mutagenic and Reprotoxic, or Substances Toxic Substances 1976/769/ EC	✓
California Proposition 65	
FDA 21 CFR Part 175.300 – Indirect Food Contact – Resinous and Polymeric Coatings	✓
European Food Directive 1935/2004/EC	✓
Foodstuffs and Consumer Goods Act and LFGB approved	✓
Halogen free	
Latex free	
Animal derivatives free	
BP Free	✓

Stocked Sizes Available for the following Zebra Printers:

ZT220, desktop, mid-range and high-performance thermal printers, Zebra engines, other legacy Zebra printers (Other widths/lengths are available on request subject to minimum order quantities and lead times)

Recommended Storage Conditions:

1 year duration when stored at -5°C to 40°C (23°F to 104°F) at 20% to 85% RH

3200 Barcode Scannability

The below scannability testing was performed on Z4M, 140XiIII, 90XiIII, 170XiIII, 105SL and Stripe 600.

Label Facestock	Print Speed	Barcode	Lab Results
Coated paper labels and tags	Up to 254mm/sec	10 or 12 mil normal code	Typical ANSI Grade A
Synthetics	Up to 203.3mm/sec	10 or 12 mil normal code	Typical ANSI Grade A
Uncoated paper labels and tags	Up to 152.4mm/sec	10 or 12 mil normal code	Typical ANSI Grade B
Coated paper labels and tags	Up to 254mm/sec	15 mil rotated code	Typical ANSI Grade B
Synthetics	Up to 203.2mm/sec	15 mil rotated code	Typical ANSI Grade B

Performance Analysis

All of the below tests were performed on Z-Xtreme™ 4000T White using 10 cycles (20 rubs) with the Crockmeter.

Test Solvents	Zebra 3200 Performance
Glass Cleaner w/Ammonia	✓
Formula 409	✓
Motor Oil	
Brake Fluid	^
Gunk Degreaser	^
WD-40	^
Genesolv	
Hexane	^
Xylene	✓
Gasoline	^
Acetone	
Alcohol (90% Isopropyl Alcohol)	✓

✓: Scanning received a “B” ANSI grade or above.

^ : Scanning received a “C” to “F” ANSI grade.

Blank: Barcode does not scan



Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

All products should be pre-tested to ensure they meet all intended requirements of specific end-use applications.

For testing of this ribbon on Zebra mid-range and high-performance printers please order part number 03200BK11005. For testing on other printer models, please contact your Supplies Specialist representative.